Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCALEOVIEW L17-1
17 Inch LCD Display

Issue May 2006

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. Sleek and space-saving, the SCALEOVIEW L17-1 is the best choice LCD for families. It offers best performance for the home office and multimedia such as photo editing, gaming and watching the latest DVDs. It is the ideal LCD for those seeking to upgrade their bulky CRT with limited budget.

Highlights

- 17-inch display for a perfect viewing experience
- Best performance to an affordable price
- High-end connectivity with 2 analogue and 1 DVI connector
- Stylish black design with an ultra slim aluminum front
- Desk and keyboard illumination with small light in front
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent color purity
- Well balanced brightness uniformity
- Excellent high contrast 500:1
- Space saving design

Technical highlights

17” (43cm) LCD Display	
Excellent contrast	500:1
Brightness	260 cd/m^2
Fast response time (typ.)	8ms

Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability

Visible screen diagonal	17 inch (43 cm)
Resolution	
Pixels	1280 x 1024
Pixels*	1024 x 768
Pixels*	800 x 600
* expanded	
Picture size	338 x 270 mm
Colors	16.2 million
Pixel Pitch	0.264 mm
Frequencies	
Horizontal	30 - 80 kHz
Vertical	60 - 75 Hz
Brightness (typical)	260 cd/m²
Contrast (typical)	500:1
Viewing angle (typical)	
Horizontal	150°
Vertical	130°
Response time (typical)	8 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light)	
Contrast	
Volume control	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, Spanish, French, Italian, Russian, Swedish, Portuguese, Danish, Polish, Finnish	
Base	
Tilt angle	-5° / +20°
Video input	1 x D-SUB, 1x DVI-D
Audio characteristics	
Audio signal input	3.5mm stereo phone jack
Audio output	2.5 W (L) + 2.5 W (R)

Electrical values (internal power supply)	
Rated voltage	100 - 240 V
Frequency	47 - 63 Hz
Power draw	
Max.	< 60 W
Stand by	< 2 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	15°C to 32°C
Storage	-20°C to 60°C
Dimensions (H x W x D): (With Stand)	404 x 410 x 152 mm
Weight (Monitor only):	3.5 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	50,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN50082-1 EN61000-3-2/-3) TCO'03
Accessories	
Power cable (1.5 m)*	For wall socket Euro-Schuko-Type CEE7
Plug type on Monitor	IEC-320-C13
Data cable (1.5 m)*	1 x D-SUB (15-pin)
Audio Cable (1.8m)*	3.5mm stereo phone jack
* detachable on display	
Special features	
Standardized mounting interface according VESA FPMPMI (100 mm) Integrated audio Kensington Lock	
Order code	S26361-K1102-V170 EAN: 4045827665182

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers, 05/2006

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp